

EVAC outdoor column speakers - EC4PT4G200

TUTONDO®



EC4PT4M200



EC4PT4G200

Column acoustic speaker with modular system, EN 54-24 certified.

Composed of 1 mid-low unit with 3 adjustable setting filters. High unit composed by one waveguide double horn unit, with two 20W RMS driver.

In this way we get the most suitable response in power and coverage for each architectural solution, where the speaker is requested to solve intelligibility problems, sound pressure and in the same time it must be easily integrated into environments.

Suitable for ceiling and wall mount, plasterboard or bearing tubular architectures for both internal and external installations.

Stainless steel case painted in Oyster White colour, with speakers protected by a metal mesh, complete with fixing brackets. Front speaker protected by double layer wire mesh, with protection level IP65.

Junction box for connecting the wires complete with 2 clamps PG type. EN54-24 certified have thermal fuse protection and ceramic double terminals for separate connections.

Also available optional brackets kit ([SCPO](#) and [SCPOV](#)) for the installation of columns composed of several modules.

Model specification

TUTONDO

a brand of **A.T.E.C. Srl**
Via Nobel, 8 30020 - Noventa di Piave / Venezia - Italy
T +39 0421 65288 / F +39 0421 659017 / www.tutondo.com

EVAC outdoor column speakers - EC4PT4G200

TUTONDO®

Column acoustic speaker with modular system, EN 54-24 certified.

Composed of 1 broadband unit with 3 adjustable setting filters, and 1 high unit composed by one waveguide double horn unit, with driver. 100V, 200+48 W, SPL max 116,2, response 160-20000 Hz, coverage angle 360°x60°.

Painted stainless steel case, with speakers protected by a metal mesh, complete with fixing brackets.

Front speaker protected by double layer wire mesh, with protection level IP65.

Junction box for connecting the wires complete with 2 clamps PG11 type, thermal fuse protection and ceramic double terminals for separate connections.

Weight: 10,7 kg.

Size: H680 x W115 x D160 mm.

Colour: RAL 9003.

Technical features

System	100V
Power [Wrms]	200 + 48
Impedance [ohm]	-
Frequency range [Hz]	160÷20000
SPL [1W/1m]	93,2dB
SPL MAX	116,2dB
Coverage angle [degrees]	
Weight [kg]	10,7Kg
Dimensions [mm]	H680 x W115 x D160mm

Available variants

No available variants

Technical draw

EVAC outdoor column speakers - EC4PT4G200

TUTONDO®



Connection diagram

EVAC outdoor column speakers -
EC4PT4G200

TUTONDO®

