



Bidirectional acoustic speaker with 2 broadband 5" loudspeakers. Different models available in white, black or chrome metal.

### Model specification

On-wall or on-ceiling bi-directional speaker for indoor or protected outdoor purposes, 100V, 12W, EN54-24 certified.

On-wall or on-ceiling bi-directional speaker, rectangular shape, ABS V0 structure and micro drilled grid for speaker protection, for indoor or protected outdoor purposes in accordance with EN54-24, with a wide band 2 x 5" double cone speaker, linear audio transformer for connection to 100V constant voltage lines, thermal fuse protection of the line in case of overheating, ceramic type double terminals for separate connections (line input and line output).

Metal junction box for on-wall or on-ceiling fixing and for connecting the wires to the terminals of the input and output lines complete with 2 clamps PG11 type.

Weight: 1,7 kg.

# Rio bidirectional EN54-24 - ERRT4M

TUTONDO®

Dimensions: H 286 x W 174 x D 105 mm.  
Colors: White (B), Black (N), Silver (MC).

## Technical features

System	100V EN54-24
Power [Wrms]	12
Impedance [ohm]	833 Ω
Frequency range [Hz]	-
SPL [1W/1m]	83dB
SPL MAX	94dB
Coverage angle [degrees]	-
Weight [kg]	1.7kg
Dimensions [mm]	H286 x W194 x D105mm

## Available variants

### Bidirectional Rio Colors

- ERRT4MB: White
- ERRT4MMC: Chrome Metal
- ERRT4MN: Black